

EBA SERIES



Model		EBA-32/34 SERIES	EB-200	EBA-21-SD2	EBA-21/22 SERIES
Banknote size in mm:	Width	62~85	62~77	62~78	62~78 (EMA 21), 62~85
	Length	120~160	118~160	125~170	
Acceptance rate		no less than 95% (incl. auto-retry up to 2 times)	90% normal acceptance 95% high acceptance	no less than 90%	no less than 90%
Validation speed in seconds		approx. 3 (excluding auto-retry)	approx. 2	approx. 6	approx. 3.5
Escrow – one banknote		yes	yes	yes	yes
Interface:	Serial	yes	yes	yes	yes
	MDB	yes (EBA-34)	option	option	option
	cctalk	yes (EBA-32)	–	–	yes
	HII	on request (EBA 32)	–	–	–
	RS-232C	option	option	option	option
	Pulse	–	yes	yes	yes
	Parallel	–	–	yes	yes
Lockable type cash box		semi security	no	semi security	–
Removable type cash box		yes	no	yes	–
Stacker capacity		400 (SD3)	400	400/600 <small>option</small>	–
Power requirement		DC12V (± 5%)	DC12V (± 5%)	DC12V (± 5%)	DC 2V (± 5%)
Standby/Operating		280mA/2.5A	340mA/1.0A	420mA/680mA	250mA/500mA
Temperature:	Operation	5~50° C	5~50° C	0~40° C	0~40° C
	Storage	–20~+60° C	–20~+60° C	–20~+70° C	–20~+70° C
Humidity <small>(no condensation)</small>		30~85%	30~85%	30~85%	30~85%
Dimension approx. W x D x H in mm		116x197x317 (head 86)	93x223x180	106x214x359	108x208x88.5 116x208x88,5 (EBA-22)
Weight approx. in kg		2.5 (head 1.0)	1.3	4.0	1.2
Installation		indoor	indoor	indoor	indoor
Approvals		CE	CE	CE	CE